

## ICE mini Specifications

Lens size	Dia. 80 mm or less	
Layout span	FPD	: 30.0 - 99.5 mm
	PD (or 1/2 PD)	: 30.0 - 99.5 mm (15.0 - 49.75 mm)
	Height of the optical center	: 0 - ± 15.0 mm
	Size adjustment	: 0 - ± 9.95mm
Item to be entered	FPD	
	PD (or 1/2 PD)	
	Height of the optical center (↓, BT↓, PD↓)	
	Lens size	
	Lens material (Plastic lens, Plastic lens with high refractive index, Glass lens, Polycarbonate lens, Acrylic lens, TRIVEX lens)	
	Frame type (Metal frame, Celluloid frame, Nylon frame, Rimless frame)	
	Grinding mode selection	
Job code		
Blocking method	Manual blocking method	
Blocking accuracy	Position	: Dia. 0.5 mm or less
	Axis angle	: ± 0.5° or less
Interface	4 RS-232C, 1 LAN (10BASE-T)	
Memory	30 jobs, 200 patterns	
	(The number of memory data can be increased using an optional USB memory.)	
Display	8.4-inch color LCD touch panel	
Power supply	AC 100 - 120 V / 230 V	
	50 / 60 Hz	
Power consumption	35 VA	
Dimensions & weight	230 (W) x 367 (D) x 292 (H) mm / 8 kg	
	9.05 (W) x 14.45 (D) x 11.5 (H) " / 17.6 lbs.	
Standard accessories	Spare fuse (x2), Interface cable (x1), Touch-panel pencil (x1), Power cord (x1)	
Optional accessories	Barcode scanner, USB memory	



Eye & Health Care  
**NIDEK CO., LTD.**

## HEAD OFFICE

34-14 Maehama, Hiroishi  
Gamagori, Aichi 443-0038, Japan  
Telephone : 81-533-67-6611  
Facsimile : 81-533-67-6610  
URL : <http://www.nidek.co.jp>

## TOKYO OFFICE

(International Div.)  
6F Takahashi Bldg.,  
3-2 Kanda-Jinboucho  
Chiyoda, Tokyo 101-0051, Japan  
Telephone : 81-3-3288-0571  
Facsimile : 81-3-3288-0570  
URL : <http://www.nidek.com>

## NIDEK INC.

47651 Westinghouse Drive  
Fremont, CA 94539, U.S.A.  
Telephone : 1-510-226-5700  
: 1-800-223-9044 (US only)  
Facsimile : 1-510-226-5750  
URL : <http://www.usa.nidek.com>

## NIDEK SOCIÉTÉ ANONYME

Europarc  
13, rue Auguste Perret  
94042 Créteil, France  
Telephone : 33-1-49 80 97 97  
Facsimile : 33-1-49 80 32 08  
URL : <http://www.nidek.fr>

## NIDEK TECHNOLOGIES SRL

Via dell'Artigianato, 6 / A  
35020 Albignasego (Padova), Italy  
Telephone : 39 049 8629200 / 8626399  
Facsimile : 39 049 8626824  
URL : <http://www.nidektechnologies.it>

*Quick and Easy Blocking*

# ICE mini

INTELLIGENT BLOCKER



\*Specifications and design are subject to change without notice for improvement.



Printed on environment-friendly recycled paper.

©NIDEK 2006 Printed in Japan ICE-mini NODIM®






## ■ User-friendly LCD Touch Panel

8.4-inch color LCD touch panel offers clear display and easy operation.

Traced actual outline and finished outline of the lens are simultaneously displayed in actual size, which is quite useful when determining if the external outline is sufficient for the traced outline.



## ■ Versatile Network Capability

The ICE mini can be directly connected to a lens edger as a minimum configuration. The traced data obtained with the built-in tracer of the LE-9000 are automatically stored into the ICE mini's internal memory.

You can also connect several devices like the NIDEK LT-900 frame tracer and SE-9090 Express lab edger on a local-area network (LAN) for medium to mass productions of finished lenses. Various system configurations are possible to meet each customer's needs.

### Minimum Configuration



### Mini LAB Configuration



\*These configurations are just examples. Please contact NIDEK for further information.

# Intelligent Blocker ICE mini

## ■ Quick and Easy Blocking

**STEP 1.** Simply place the marked lens on the table.



**STEP 2.** Input all data on the LCD touch panel. The data to be input are the lens type, frame type, grinding mode and lens layout data which includes FPD, PD, height of optical center and size.



**STEP 3.** Block with the blocking arm. Flexible 3-pin lens support, holding the lens from the top, greatly helps the operator to achieve easy and accurate blocking.



Blocking